



**Manu. & Mrkt. :**

**Air Compressores, Spreyer Pump, Cut off Machine, Electric Air Blower,  
Electric Motor, Jigsaw Machine, Bench Grinder.**

Products

Catalogue 2022



**A Quality Products**





SP-1

Single Cylinder Single Stage Air Compressor

| MODEL | H.P. | R.P.M. | TANK SIZE |           |        |                | WORKING PRESSURE |                      | BOR x STROKE | PISTON DISPLACEMENT | APROX WEIGHT W/O MOTOR |
|-------|------|--------|-----------|-----------|--------|----------------|------------------|----------------------|--------------|---------------------|------------------------|
|       |      |        | IN INCH   | IN LITERS | IN PSI | Tank Thickness | PSI              | Kg / CM <sup>2</sup> | MM           | CFM                 | Kg.                    |
| SP-1  | 0.5  | 750    | 8 x 24    | 20        | 60     | 2.5mm          | 100              | 7                    | 52mm x 40mm  | 2.7                 | 33                     |
| SSP-1 | 0.5  | 750    | 10 X 28   | 35        | 100    | 2.5mm          | 100              | 7                    | 52mm x 40mm  | 2.7                 | 39                     |



SP-2

Single Cylinder Single Stage Air Compressor

| MODEL | H.P. | R.P.M. | TANK SIZE |           |        |                | WORKING PRESSURE |                      | BOR x STROKE | PISTON DISPLACEMENT | APROX WEIGHT W/O MOTOR |
|-------|------|--------|-----------|-----------|--------|----------------|------------------|----------------------|--------------|---------------------|------------------------|
|       |      |        | IN INCH   | IN LITERS | IN PSI | Tank Thickness | PSI              | Kg / CM <sup>2</sup> | MM           | CFM                 | Kg.                    |
| SP-2  | 0.5  | 750    | 10 X 28   | 35        | 100    | 2.5mm          | 125              | 8                    | 57mm x 40mm  | 3.5                 | 41                     |
| SSP-2 | 0.5  | 750    | 11 X 28   | 45        | 150    | 2.5mm          | 125              | 8                    | 57mm x 40mm  | 3.5                 | 43                     |



SP-3

Single Cylinder Single Stage Air Compressor

| MODEL  | H.P. | R.P.M. | TANK SIZE |           |        |                | WORKING PRESSURE |                      | BOR x STROKE   | PISTON DISPLACEMENT | APROX WEIGHT W/O MOTOR |
|--------|------|--------|-----------|-----------|--------|----------------|------------------|----------------------|----------------|---------------------|------------------------|
|        |      |        | IN INCH   | IN LITERS | IN PSI | Tank Thickness | PSI              | Kg / CM <sup>2</sup> | MM             | CFM                 | Kg.                    |
| SP-3   | 1    | 750    | 11 X 32   | 50        | 150    | 2.5mm          | 150              | 10                   | 63mm x 50.8 mm | 4.5                 | 51                     |
| SSP-3  | 1    | 750    | 12 X 32   | 60        | 200    | 2.5mm          | 150              | 10                   | 63mm x 50.8 mm | 4.5                 | 53                     |
| SSSP-3 | 1    | 750    | 14 X 32   | 85        | 250    | 2.5mm          | 150              | 10                   | 63mm x 50.8 mm | 4.5                 | 59                     |
| SPSP-3 | 1    | 750    | 15 X 38   | 110       | 300    | 3mm            | 150              | 10                   | 63mm x 50.8 mm | 4.5                 | 65                     |



SP-4

## Single Cylinder Single Stage Air Compressor

| MODEL  | H.P. | R.P.M. | TANK SIZE |           |        |                | WORKING PRESSURE |                      | BOR x STROKE   | PISTON DISPLACEMENT | APROX WEIGHT W/O MOTOR |
|--------|------|--------|-----------|-----------|--------|----------------|------------------|----------------------|----------------|---------------------|------------------------|
|        |      |        | IN INCH   | IN LITERS | IN PSI | Tank Thickness | PSI              | Kg / CM <sup>2</sup> | MM             | CFM                 | Kg.                    |
| SP-4   | 1    | 750    | 12 x 32   | 60        | 200    | 2.5mm          | 150              | 10                   | 63mm x 57.15mm | 5.15                | 59                     |
| SSP-4  | 1    | 750    | 14 X 32   | 85        | 250    | 2.5mm          | 150              | 10                   | 63mm x 57.15mm | 5.15                | 63                     |
| SSSP-4 | 1    | 750    | 15 x 38   | 110       | 300    | 3mm            | 150              | 10                   | 63mm x 57.15mm | 5.15                | 73                     |
| SPSP-4 | 1    | 750    | 16 X 40   | 135       | 350    | 3mm            | 150              | 10                   | 63mm x 57.15mm | 5.15                | 79                     |



SP-5

## Single Cylinder Single Stage Air Compressor

| MODEL  | H.P. | R.P.M. | TANK SIZE |           |        |                | WORKING PRESSURE |                      | BOR x STROKE   | PISTON DISPLACEMENT | APROX WEIGHT W/O MOTOR |
|--------|------|--------|-----------|-----------|--------|----------------|------------------|----------------------|----------------|---------------------|------------------------|
|        |      |        | IN INCH   | IN LITERS | IN PSI | Tank Thickness | PSI              | Kg / CM <sup>2</sup> | MM             | CFM                 | Kg.                    |
| SP-5   | 1.5  | 750    | 14 X 32   | 85        | 250    | 2.5mm          | 170              | 12                   | 70mm x 57.15mm | 6.10                | 63                     |
| SSP-5  | 1.5  | 750    | 15 X 38   | 110       | 300    | 3mm            | 170              | 12                   | 70mm x 57.15mm | 6.10                | 73                     |
| SSSP-5 | 1.5  | 750    | 16 X 40   | 135       | 350    | 3mm            | 170              | 12                   | 70mm x 57.15mm | 6.10                | 80                     |



SP-6

## Single Cylinder Single Stage Air Compressor

| MODEL  | H.P. | R.P.M. | TANK SIZE |           |        |                | WORKING PRESSURE |                      | BOR x STROKE   | PISTON DISPLACEMENT | APROX WEIGHT W/O MOTOR |
|--------|------|--------|-----------|-----------|--------|----------------|------------------|----------------------|----------------|---------------------|------------------------|
|        |      |        | IN INCH   | IN LITERS | IN PSI | Tank Thickness | PSI              | Kg / CM <sup>2</sup> | MM             | CFM                 | Kg.                    |
| SP-6   | 2    | 750    | 15 X 38   | 110       | 300    | 3mm            | 170              | 12                   | 65mm x 88.9 mm | 8.85                | 85                     |
| SSP-6  | 2    | 750    | 16 X 40   | 135       | 350    | 3mm            | 170              | 12                   | 65mm x 88.9 mm | 8.85                | 92                     |
| SSSP-6 | 2    | 750    | 18 X 40   | 175       | 375    | 4mm            | 170              | 12                   | 65mm x 88.9 mm | 8.85                | 119                    |
| SPSP-6 | 2    | 750    | 18 X 44   | 190       | 400    | 4mm            | 170              | 12                   | 65mm x 88.9 mm | 8.85                | 125                    |



## DSP-1

### Double Cylinder Single Stage Air Compressor

| MODEL   | H.P. | R.P.M. | TANK SIZE |           |        |                | WORKING PRESSURE |                      | BOR x STROKE  | PISTON DISPLACEMENT | APROX WEIGHT W/O MOTOR |
|---------|------|--------|-----------|-----------|--------|----------------|------------------|----------------------|---------------|---------------------|------------------------|
|         |      |        | IN INCH   | IN LITERS | IN PSI | Tank Thickness | PSI              | Kg / CM <sup>2</sup> |               |                     |                        |
| DSP-1   | 1    | 750    | 12 x 32   | 60        | 200    | 3mm            | 150              | 10                   | 57mm x 50.8mm | 5.0                 | 64                     |
| SDSP-1  | 1    | 750    | 14 X 32   | 85        | 250    | 3mm            | 150              | 10                   | 57mm x 50.8mm | 5.0                 | 69                     |
| SSDSP-1 | 1    | 750    | 15 x 38   | 110       | 300    | 3mm            | 150              | 10                   | 57mm x 50.8mm | 5.0                 | 79                     |



## DSP-1A

### Double Cylinder Single Stage Air Compressor

| MODEL      | H.P. | R.P.M. | TANK SIZE |           |        |                | WORKING PRESSURE |                      | BOR x STROKE    | PISTON DISPLACEMENT | APROX WEIGHT W/O MOTOR |
|------------|------|--------|-----------|-----------|--------|----------------|------------------|----------------------|-----------------|---------------------|------------------------|
|            |      |        | IN INCH   | IN LITERS | IN PSI | Tank Thickness | PSI              | Kg / CM <sup>2</sup> |                 |                     |                        |
| PDSP-1(A)  | 1    | 750    | 10 X 28   | 35        | 100    | 3mm            | 100              | 7                    | 50.8mm x 50.8mm | 5.25                | 53                     |
| DSP-1(A)   | 1    | 750    | 11 x 32   | 50        | 150    | 3mm            | 100              | 7                    | 50.8mm x 50.8mm | 5.25                | 57                     |
| SDSP-1(A)  | 1    | 750    | 12 X 32   | 60        | 200    | 3mm            | 100              | 7                    | 50.8mm x 50.8mm | 5.25                | 59                     |
| SSDSP-1(A) | 1    | 750    | 14 x 32   | 85        | 250    | 3mm            | 100              | 7                    | 50.8mm x 50.8mm | 5.25                | 65                     |
| SPDSP-1(A) | 1    | 750    | 15 X 38   | 110       | 300    | 3mm            | 100              | 7                    | 50.8mm x 50.8mm | 5.25                | 72                     |





## DSP-2

### Double Cylinder Single Stage Air Compressor

| MODEL   | H.P. | R.P.M. | TANK SIZE |           |        |                | WORKING PRESSURE |                      | BOR x STROKE   | PISTON DISPLACEMENT | APROX WEIGHT W/O MOTOR |
|---------|------|--------|-----------|-----------|--------|----------------|------------------|----------------------|----------------|---------------------|------------------------|
|         |      |        | IN INCH   | IN LITERS | IN PSI | Tank Thickness | PSI              | Kg / CM <sup>2</sup> |                |                     |                        |
| DSP-2   | 1.50 | 750    | 14 x 32   | 85        | 250    | 3mm            | 150              | 10                   | 63mm x 57.15mm | 7.60                | 73                     |
| SDSP-2  | 1.50 | 750    | 15 X 38   | 110       | 300    | 3mm            | 150              | 10                   | 63mm x 57.15mm | 7.60                | 82                     |
| SSDSP-2 | 1.50 | 750    | 16 x 40   | 135       | 350    | 3mm            | 150              | 10                   | 63mm x 57.15mm | 7.60                | 91                     |



## DSP-3

### Double Cylinder Single Stage Air Compressor

| MODEL   | H.P. | R.P.M. | TANK SIZE |           |        |                | WORKING PRESSURE |                      | BOR x STROKE   | PISTON DISPLACEMENT | APROX WEIGHT W/O MOTOR |
|---------|------|--------|-----------|-----------|--------|----------------|------------------|----------------------|----------------|---------------------|------------------------|
|         |      |        | IN INCH   | IN LITERS | IN PSI | Tank Thickness | PSI              | Kg / CM <sup>2</sup> |                |                     |                        |
| DSP-3   | 2    | 750    | 15 x 38   | 110       | 300    | 3mm            | 160              | 11                   | 65mm x 57.15mm | 8.85                | 84                     |
| SDSP-3  | 2    | 750    | 16 X 40   | 135       | 350    | 3mm            | 160              | 11                   | 65mm x 57.15mm | 8.85                | 90                     |
| SSDSP-3 | 2    | 750    | 18 x 40   | 175       | 375    | 4mm            | 160              | 11                   | 65mm x 57.15mm | 8.85                | 118                    |



## DSP-3A

### Double Cylinder Single Stage Air Compressor

| MODEL      | H.P. | R.P.M. | TANK SIZE |           |        |                | WORKING PRESSURE |                      | BOR x STROKE  | PISTON DISPLACEMENT | APROX WEIGHT W/O MOTOR |
|------------|------|--------|-----------|-----------|--------|----------------|------------------|----------------------|---------------|---------------------|------------------------|
|            |      |        | IN INCH   | IN LITERS | IN PSI | Tank Thickness | PSI              | Kg / CM <sup>2</sup> |               |                     |                        |
| DSP-3(A)   | 2    | 750    | 15 x 38   | 110       | 300    | 3mm            | 150              | 10                   | 63.5mm x 68mm | 9.15                | 92                     |
| SDSP-3(A)  | 2    | 750    | 16 X 40   | 135       | 350    | 3mm            | 150              | 10                   | 63.5mm x 68mm | 9.15                | 100                    |
| SSDSP-3(A) | 2    | 750    | 18 x 40   | 175       | 375    | 4mm            | 150              | 10                   | 63.5mm x 68mm | 9.15                | 126                    |
| SPDSP-3(A) | 2    | 750    | 18 X 44   | 190       | 400    | 4mm            | 150              | 10                   | 63.5mm x 68mm | 9.15                | 132                    |



## DSP-4

### Double Cylinder Single Stage Air Compressor

| MODEL   | H.P. | R.P.M. | TANK SIZE |           |        |                | WORKING PRESSURE |                      | BOR x STROKE | PISTON DISPLACEMENT | APROX WEIGHT W/O MOTOR |
|---------|------|--------|-----------|-----------|--------|----------------|------------------|----------------------|--------------|---------------------|------------------------|
|         |      |        | IN INCH   | IN LITERS | IN PSI | Tank Thickness | PSI              | Kg / CM <sup>2</sup> |              |                     |                        |
| DSP-4   | 2    | 750    | 15 x 38   | 110       | 300    | 3mm            | 170              | 12                   | 65mm x 70mm  | 10.5                | 90                     |
| SDSP-4  | 2    | 750    | 16 X 40   | 135       | 350    | 3mm            | 170              | 12                   | 65mm x 70mm  | 10.5                | 96                     |
| SSDSP-4 | 2    | 750    | 18 x 40   | 175       | 375    | 4mm            | 170              | 12                   | 65mm x 70mm  | 10.5                | 123                    |
| SPDSP-4 | 2    | 750    | 18 X 44   | 190       | 400    | 4mm            | 170              | 12                   | 65mm x 70mm  | 10.5                | 130                    |



## DSP-4H

### Double Cylinder Single Stage Air Compressor

| MODEL    | H.P. | R.P.M. | TANK SIZE |           |        |                | WORKING PRESSURE |                      | BOR x STROKE | PISTON DISPLACEMENT | APROX WEIGHT W/O MOTOR |
|----------|------|--------|-----------|-----------|--------|----------------|------------------|----------------------|--------------|---------------------|------------------------|
|          |      |        | IN INCH   | IN LITERS | IN PSI | Tank Thickness | PSI              | Kg / CM <sup>2</sup> |              |                     |                        |
| DSP-4H   | 2    | 650    | 15 x 38   | 110       | 300    | 3mm            | 150              | 10                   | 60mm x 60mm  | 8.3                 | 90                     |
| SDSP-4H  | 2    | 650    | 16 x 40   | 135       | 350    | 3mm            | 150              | 10                   | 60mm x 60mm  | 8.3                 | 96                     |
| SSDSP-4H | 2    | 650    | 18 x 40   | 175       | 375    | 3mm            | 150              | 10                   | 60mm x 60mm  | 8.3                 | 123                    |
| SPDSP-4H | 2    | 650    | 18 x 44   | 190       | 400    | 3mm            | 150              | 10                   | 60mm x 60mm  | 8.3                 | 130                    |

## DSP-5H

|          |   |     |         |     |     |     |     |    |             |      |     |
|----------|---|-----|---------|-----|-----|-----|-----|----|-------------|------|-----|
| DSP-5H   | 3 | 725 | 16 x 40 | 135 | 350 | 3mm | 170 | 12 | 70mm x 70mm | 14.1 | 101 |
| SDSP-5H  | 3 | 725 | 18 x 40 | 175 | 375 | 4mm | 170 | 12 | 70mm x 70mm | 14.1 | 141 |
| SSDSP-5H | 3 | 725 | 18 x 44 | 190 | 400 | 4mm | 170 | 12 | 70mm x 70mm | 14.1 | 151 |
| SPDSP-5H | 3 | 725 | 18 x 54 | 225 | 450 | 4mm | 170 | 12 | 70mm x 70mm | 14.1 | 170 |



## DSP-5

### Double Cylinder Single Stage Air Compressor

| MODEL   | H.P. | R.P.M. | TANK SIZE |           |        |                | WORKING PRESSURE |                      | BOR x STROKE | PISTON DISPLACEMENT | APROX WEIGHT W/O MOTOR |
|---------|------|--------|-----------|-----------|--------|----------------|------------------|----------------------|--------------|---------------------|------------------------|
|         |      |        | IN INCH   | IN LITERS | IN PSI | Tank Thickness | PSI              | Kg / CM <sup>2</sup> |              |                     |                        |
| PDSP-5  | 3    | 750    | 16 x 40   | 135       | 350    | 3mm            | 170              | 12                   | 70mm x 70mm  | 14.5                | 105                    |
| DSP-5   | 3    | 750    | 18 x 40   | 175       | 375    | 4mm            | 170              | 12                   | 70mm x 70mm  | 14.5                | 130                    |
| SDSP-5  | 3    | 750    | 18 x 44   | 190       | 400    | 4mm            | 170              | 12                   | 70mm x 70mm  | 14.5                | 138                    |
| SSDSP-5 | 3    | 750    | 18 x 54   | 225       | 450    | 4mm            | 170              | 12                   | 70mm x 70mm  | 14.5                | 160                    |
| SPDSP-5 | 3    | 750    | 20 x 52   | 300       | 500    | 5mm            | 170              | 12                   | 70mm x 70mm  | 14.5                | 185                    |



## DSP-6

### Double Cylinder Single Stage Air Compressor

| MODEL   | H.P. | R.P.M. | TANK SIZE |           |        |                | WORKING PRESSURE |                      | BOR x STROKE   | PISTON DISPLACEMENT | APROX WEIGHT W/O MOTOR |
|---------|------|--------|-----------|-----------|--------|----------------|------------------|----------------------|----------------|---------------------|------------------------|
|         |      |        | IN INCH   | IN LITERS | IN PSI | Tank Thickness | PSI              | Kg / CM <sup>2</sup> |                |                     |                        |
| DSP-6   | 5    | 750    | 18 x 54   | 225       | 450    | 4mm            | 170              | 12                   | 80mm x 2.3/4mm | 16                  | 190                    |
| SDSP-6  | 5    | 750    | 20 X 52   | 300       | 500    | 5mm            | 170              | 12                   | 80mm x 2.3/4mm | 16                  | 215                    |
| SSDSP-6 | 5    | 750    | 20 x 60   | 325       | 550    | 5mm            | 170              | 12                   | 80mm x 2.3/4mm | 16                  | 225                    |



## DSPT-4

### Double Cylinder Double Stage Air Compressor

| MODEL   | H.P. | R.P.M. | TANK SIZE |           |        |                | WORKING PRESSURE |                      | BOR x STROKE        | PISTON DISPLACEMENT | APROX WEIGHT W/O MOTOR |
|---------|------|--------|-----------|-----------|--------|----------------|------------------|----------------------|---------------------|---------------------|------------------------|
|         |      |        | IN INCH   | IN LITERS | IN PSI | Tank Thickness | PSI              | Kg / CM <sup>2</sup> |                     |                     |                        |
| DSPT-4  | 3    | 720    | 16 x 40   | 135       | 350    | 4mm            | 175              | 12.3                 | 3"x 1 3/4" x 2 3/4" | 12.1                | 105                    |
| SDSPT-4 | 3    | 720    | 18 x 44   | 190       | 400    | 4mm            | 175              | 12.3                 | 3"x 1 3/4" x 2 3/4" | 12.1                | 135                    |





## DSPT-4H

### Double Cylinder Double Stage Air Compressor

| MODEL    | H.P. | R.P.M. | TANK SIZE |           |        |                | WORKING PRESSURE |                      | BOR x STROKE         | PISTON DISPLACEMENT | APROX WEIGHT W/O MOTOR |
|----------|------|--------|-----------|-----------|--------|----------------|------------------|----------------------|----------------------|---------------------|------------------------|
|          |      |        | IN INCH   | IN LITERS | IN PSI | Tank Thickness | PSI              | Kg / CM <sup>2</sup> |                      |                     |                        |
| DSPT-4H  | 3    | 720    | 16 x 40   | 135       | 350    | 4mm            | 175              | 12.3                 | 3" x 1 3/4" x 2 3/4" | 12.1                | 105                    |
| SDSPT-4H | 3    | 720    | 18 X 44   | 190       | 400    | 4mm            | 175              | 12.3                 | 3" x 1 3/4" x 2 3/4" | 12.1                | 135                    |



## DSPT-5

### Double Cylinder Double Stage Air Compressor

| MODEL    | H.P. | R.P.M. | TANK SIZE |           |        |                | WORKING PRESSURE |                      | BOR x STROKE         | PISTON DISPLACEMENT | APROX WEIGHT W/O MOTOR |
|----------|------|--------|-----------|-----------|--------|----------------|------------------|----------------------|----------------------|---------------------|------------------------|
|          |      |        | IN INCH   | IN LITERS | IN PSI | Tank Thickness | PSI              | Kg / CM <sup>2</sup> |                      |                     |                        |
| DSPT-5   | 5    | 720    | 18 x 54   | 225       | 450    | 5mm            | 175              | 12.3                 | 4" x 2 1/2" x 2 3/4" | 17.3                | 192                    |
| SDSPT-5  | 5    | 720    | 20 x 52   | 300       | 500    | 5mm            | 175              | 12.3                 | 4" x 2 1/2" x 2 3/4" | 17.3                | 215                    |
| SSDSPT-5 | 5    | 720    | 20 x 60   | 325       | 525    | 5mm            | 175              | 12.3                 | 4" x 2 1/2" x 2 3/4" | 17.3                | 230                    |



## DSPT-5H

### Double Cylinder Double Stage Air Compressor

| MODEL     | H.P. | R.P.M. | TANK SIZE |           |        | WORKING PRESSURE |                      |                | BOR x STROKE         | PISTON DISPLACEMENT | APROX WEIGHT W/O MOTOR |
|-----------|------|--------|-----------|-----------|--------|------------------|----------------------|----------------|----------------------|---------------------|------------------------|
|           |      |        | IN INCH   | IN LITERS | IN PSI | PSI              | Kg / CM <sup>2</sup> | Tank Thickness |                      | CFM                 | Kg.                    |
| DSPT-5H   | 5    | 720    | 18 x 54   | 225       | 450    | 175              | 12.3                 | 5mm            | 4" x 2 1/2" x 2 3/4" | 17.3                | 192                    |
| SDSPT-5H  | 5    | 720    | 20 x 52   | 300       | 500    | 175              | 12.3                 | 5mm            | 4" x 2 1/2" x 2 3/4" | 17.3                | 215                    |
| SSDSPT-5H | 5    | 720    | 20 x 60   | 325       | 525    | 175              | 12.3                 | 5mm            | 4" x 2 1/2" x 2 3/4" | 17.3                | 230                    |



## DSPT-6

### Double Cylinder Double Stage Air Compressor

| MODEL   | H.P. | R.P.M. | TANK SIZE |           |        | WORKING PRESSURE |                      |                | BOR x STROKE         | PISTON DISPLACEMENT | APROX WEIGHT W/O MOTOR |
|---------|------|--------|-----------|-----------|--------|------------------|----------------------|----------------|----------------------|---------------------|------------------------|
|         |      |        | IN INCH   | IN LITERS | IN PSI | PSI              | Kg / CM <sup>2</sup> | Tank Thickness |                      | CFM                 | Kg.                    |
| DSPT-6  | 7.5  | 640    | 20 x 60   | 325       | 525    | 175              | 12.3                 | 5mm            | 5" x 2 3/4" x 3 1/2" | 27.5                | 265                    |
| SDSPT-6 | 7.5  | 640    | 20 x 66   | 350       | 550    | 175              | 12.3                 | 5mm            | 5" x 2 3/4" x 3 1/2" | 27.5                | 275                    |



## DSPT-7,8

### Double Cylinder Double Stage Air Compressor

| MODEL  | H.P. | R.P.M. | TANK SIZE |           |        |                | WORKING PRESSURE |                      | BOR x STROKE     | PISTON DISPLACEMENT | APROX WEIGHT W/O MOTOR |
|--------|------|--------|-----------|-----------|--------|----------------|------------------|----------------------|------------------|---------------------|------------------------|
|        |      |        | IN INCH   | IN LITERS | IN PSI | Tank Thickness | PSI              | Kg / CM <sup>2</sup> |                  |                     |                        |
| DSPT-7 | 10   | 720    | 20 x 66   | 350       | 550    | 5mm            | 175              | 12.3                 | 5 1/2" x 3" x 4" | 41                  | 310                    |
| DSPT-8 | 12.5 | 820    | 24 x 66   | 485       | 600    | 6mm            | 175              | 12.3                 | 5 1/2" x 3" x 4" | 46                  | 340                    |



## DSPT-9,10,11

### Double Cylinder Double Stage Air Compressor

| MODEL   | H.P. | R.P.M. | TANK SIZE |           |        |                | WORKING PRESSURE |                      | BOR x STROKE              | PISTON DISPLACEMENT | APROX WEIGHT W/O MOTOR |
|---------|------|--------|-----------|-----------|--------|----------------|------------------|----------------------|---------------------------|---------------------|------------------------|
|         |      |        | IN INCH   | IN LITERS | IN PSI | Tank Thickness | PSI              | Kg / CM <sup>2</sup> |                           |                     |                        |
| DSPT-9  | 15   | 640    | 24 x 66   | 485       | 600    | 6mm            | 175              | 12.3                 | 5" x 5" x 3 1/2" x 4"     | 64                  | 385                    |
| DSPT-10 | 20   | 760    | 24 x 66   | 485       | 600    | 6mm            | 175              | 12.3                 | 5" x 5" x 3 1/2" x 4"     | 81                  | 395                    |
| DSPT-11 | 25   | 685    | 24 x 66   | 485       | 600    | 6mm            | 175              | 12.3                 | 5 1/2" x 5 1/2" x 4" x 4" | 106                 | 425                    |





## AIR COMPRESSOR



## SERVICE PUMP





## AP 2

SERVICE PUMP



### MODEL : AP 2 (CI+CI)

|                      |                  |
|----------------------|------------------|
| Normal Pressure      | 150 PSI / 10 Bar |
| Maximum Pressure     | 300 PSI / 21 Bar |
| Pump R.P.M.          | 720 R.P.M.       |
| Stroke Length        | 20 mm            |
| Piston Diameter      | 30 mm            |
| Piston Material      | Stainless Steel  |
| Pump Material        | Cast Iron        |
| Oil Chamber Material | Cast Iron        |
| Motor HP             | 1.5 HP           |
| Approx Weight        | 18 kg            |
| Water Suction L.P.M. | 18 L.P.M.        |
| V-Belt Size          | B-36             |

## AP 3



### MODEL : AP3 (CI+CI)

|                      |                  |
|----------------------|------------------|
| Normal Pressure      | 200 PSI / 14 Bar |
| Maximum Pressure     | 400 PSI / 28 Bar |
| Pump R.P.M.          | 540 R.P.M.       |
| Stroke Length        | 20 mm            |
| Piston Diameter      | 30 mm            |
| Piston Material      | Stainless Steel  |
| Pump Material        | Cast Iron        |
| Oil Chamber Material | Cast Iron        |
| Motor HP             | 2 HP             |
| Approx Weight        | 22 kg            |
| Water Suction L.P.M. | 24 L.P.M.        |
| V-Belt Size          | B-40             |

## AP 4

SERVICE PUMP



### MODEL : AP 4 (CI+MS)

|                      |                  |
|----------------------|------------------|
| Normal Pressure      | 150 PSI / 10 Bar |
| Maximum Pressure     | 400 PSI / 28 Bar |
| Pump R.P.M.          | 720 R.P.M.       |
| Stroke Length        | 20 mm            |
| Piston Diameter      | 30 mm            |
| Piston Material      | Stainless Steel  |
| Pump Material        | Mild Steel (MS)  |
| Oil Chamber Material | Cast Iron        |
| Motor HP             | 1.5 HP           |
| Approx Weight        | 18 kg            |
| Water Suction L.P.M. | 18 L.P.M.        |
| V-Belt Size          | B-36             |

## AP 5



### MODEL : AP 5 (CI+MS)

|                      |                  |
|----------------------|------------------|
| Normal Pressure      | 200 PSI / 14 Bar |
| Maximum Pressure     | 500 PSI / 35 Bar |
| Pump R.P.M.          | 540 R.P.M.       |
| Stroke Length        | 20 mm            |
| Piston Diameter      | 30 mm            |
| Piston Material      | Stainless Steel  |
| Pump Material        | Mild Steel (MS)  |
| Oil Chamber Material | Cast Iron        |
| Motor HP             | 2 HP             |
| Approx Weight        | 23 kg            |
| Water Suction L.P.M. | 24 L.P.M.        |
| V-Belt Size          | B-40             |

SERVICE PUMP

## AP 6

SERVICE PUMP



### MODEL : AP 6 (CI+SS)

|                      |                  |
|----------------------|------------------|
| Normal Pressure      | 150 PSI / 10 Bar |
| Maximum Pressure     | 400 PSI / 28 Bar |
| Pump R.P.M.          | 720 R.P.M.       |
| Stroke Length        | 20 mm            |
| Piston Diameter      | 30 mm            |
| Piston Material      | Stainless Steel  |
| Pump Material        | Stainless Steel  |
| Oil Chamber Material | Cast Iron        |
| Motor HP             | 1.5 HP           |
| Approx Weight        | 18 kg.           |
| Water Suction L.P.M. | 18 L.P.M.        |
| V-Belt Size          | A-36             |

## AP 7



### MODEL : AP 7 (CI+SS)

|                      |                  |
|----------------------|------------------|
| Normal Pressure      | 200 PSI / 14 Bar |
| Maximum Pressure     | 500 PSI / 35 Bar |
| Pump R.P.M.          | 540 R.P.M.       |
| Stroke Length        | 20 mm            |
| Piston Diameter      | 30 mm            |
| Piston Material      | Stainless Steel  |
| Pump Material        | Stainless Steel  |
| Oil Chamber Material | Cast Iron        |
| Motor HP             | 2 HP             |
| Approx Weight        | 23 kg            |
| Water Suction L.P.M. | 24 L.P.M.        |
| V-Belt Size          | A-40             |

## AP 8

SERVICE PUMP



### MODEL : AP 8 (Alu.+MS)

|                      |                  |
|----------------------|------------------|
| Normal Pressure      | 200 PSI / 14 Bar |
| Maximum Pressure     | 500 PSI / 35 Bar |
| Pump R.P.M.          | 720 R.P.M.       |
| Stroke Length        | 20 mm            |
| Piston Diameter      | 30 mm            |
| Piston Material      | Stainless Steel  |
| Pump Material        | Mild Steel (MS)  |
| Oil Chamber Material | Aluminum         |
| Motor HP             | 1.5 HP           |
| Approx Weight        | 16 kg.           |
| Water Suction L.P.M. | 18 L.P.M.        |
| V-Belt Size          | A-36             |

## AP 9



### MODEL : AP 9 (Alu.+MS)

|                      |                  |
|----------------------|------------------|
| Normal Pressure      | 250 PSI / 18 Bar |
| Maximum Pressure     | 700 PSI / 49 Bar |
| Pump R.P.M.          | 600 R.P.M.       |
| Stroke Length        | 20 mm            |
| Piston Diameter      | 30 mm            |
| Piston Material      | Stainless Steel  |
| Pump Material        | Mild Steel (MS)  |
| Oil Chamber Material | Aluminum         |
| Motor HP             | 2 HP             |
| Approx Weight        | 22 kg.           |
| Water Suction L.P.M. | 24 L.P.M.        |
| V-Belt Size          | A-40             |

## AP 10

SERVICE PUMP



### MODEL : AP 10 (Allu.+SS)

|                      |                  |
|----------------------|------------------|
| Normal Pressure      | 200 PSI / 14 Bar |
| Maximum Pressure     | 500 PSI / 35 Bar |
| Pump R.P.M.          | 720 R.P.M.       |
| Stroke Length        | 20 mm            |
| Piston Diameter      | 30 mm            |
| Piston Material      | Stainless Steel  |
| Pump Material        | Stainless Steel  |
| Oil Chamber Material | Aluminum         |
| Motor HP             | 1.5 HP           |
| Approx Weight        | 16 kg            |
| Water Suction L.P.M. | 18 L.P.M.        |
| V-Belt Size          | A-36             |

## AP 11



### MODEL : AP 11 (Allu.+SS)

|                      |                  |
|----------------------|------------------|
| Normal Pressure      | 250 PSI / 18 Bar |
| Maximum Pressure     | 700 PSI / 49 Bar |
| Pump R.P.M.          | 600 R.P.M.       |
| Stroke Length        | 20 mm            |
| Piston Diameter      | 30 mm            |
| Piston Material      | Stainless Steel  |
| Pump Material        | Stainless Steel  |
| Oil Chamber Material | Alluminum        |
| Motor HP             | 2 HP             |
| Approx Weight        | 22 kg            |
| Water Suction L.P.M. | 24 L.P.M.        |
| V-Belt Size          | A-40             |

## AP 12

SERVICE PUMP



### MODEL : AP 12 (Allu.+MS)

|                      |                   |
|----------------------|-------------------|
| Normal Pressure      | 700 PSI / 49 Bar  |
| Maximum Pressure     | 1000 PSI / 70 Bar |
| Pump R.P.M.          | 600 R.P.M.        |
| Stroke Length        | 20 mm             |
| Piston Diameter      | 30 mm             |
| Piston Material      | Stainless Steel   |
| Pump Material        | Mild Steel (MS)   |
| Oil Chamber Material | Aluminum          |
| Motor HP             | 3 HP              |
| Approx Weight        | 27 kg             |
| Water Suction L.P.M. | 48 L.P.M.         |
| V-Belt Size          | A-40              |

## AP 13



### MODEL : AP 13 (Allu.+SS)

|                      |                   |
|----------------------|-------------------|
| Normal Pressure      | 700 PSI / 49 Bar  |
| Maximum Pressure     | 1000 PSI / 70 Bar |
| Pump R.P.M.          | 600 R.P.M.        |
| Stroke Length        | 20 mm             |
| Piston Diameter      | 30 mm             |
| Piston Material      | Stainles Steel    |
| Pump Material        | Stainles Steel    |
| Oil Chamber Material | Alluminum         |
| Motor HP             | 3 HP              |
| Approx Weight        | 27 kg             |
| Water Suction L.P.M. | 48 L.P.M.         |
| V-Belt Size          | A-40              |


SERVICE PUMP





## AIR COMPRESSORES

Speed Industrial Reciprocating Air Compressor Applications :



**Shiv Manufacturers**

Rajkot (Gujarat) -360 004  
e-mail : [shiventerprise.speed@gmail.com](mailto:shiventerprise.speed@gmail.com)  
website : [www.shiventerprise\\_speed.com](http://www.shiventerprise_speed.com)